



TECHNICAL & PRODUCT INFORMATION

TIMBERTONE

An acrylic, TRANSPARENT/OPAQUE coating/ treatment specifically developed to provide an economic alternative to solvent borne stains for fencing and rough sawn timbers. Timbertone provides good coverage and ease of application. Produced from highly durable resins and oxide pigments. Timbertone protects and decorates timber and is also available as a concentrate to suit.

CHARACTERISTICS:

- Low Viscosity, good Brush Out
- High U.V protection
- High penetration of timber
- High adhesion to timber
- Water repellent
- Rapid drying, early recoat
- Low odour
- Non-flammable
- Non toxic– safe to plants/animals
- Fungicidal protection

WHERE TO USE:

Timbertone has been developed to provide a complete protective/decorative wood coating to rough sawn timbers ie. fencing and cladding, rough– sawn and planed timbers & sheds.

Apply to rough sawn timbers by brush or roller .Timbertone should preferably be applied as a 2 coat system to achieve full protection.

Timbertone is not suitable for windows, doors, joinery and areas of high mechanical abrasion.

For extended durability, Superclad, Landscape, Excel or Shield Colour Opaque should be used.

COVERAGE:

Coverage will depend on application method timber absorbency, temperature and dilution. **DO NOT APPLY UNDER 8c**
Timbertone will normally allow between 4-6 sq meters 1st coat. Subsequent coats will provide approx. 20% increased coverage.

PACK SIZE:

5, 10 and 20lt containers
20 Litre drums. Larger size on application

REMEDIAL TREATMENT:

Remove all loose / flaking previously applied treatment from the timber. If necessary, remove any fungus or surface contamination from the timber with warm water and allow to dry. Apply Timbertone with a brush or roller. Allow to dry. If necessary, apply a second coat.

DRYING TIME:

Depending on conditions, between 20/60 mins.

DO NOT: Apply in temperatures less than 8c.

COLOURS: All woodshades and opaque colours, inc RAL and BS standards. A colour matching service is available.

ADVISORY NOTE:

Always carry out trial/test area before commencing main job/contract. Always ensure suitability beforehand, particularly where colour matching is being carried out.